

- 1/ Remove original plastic bumper, original alloy bumper reinforcement bar and plastic bumper upper retaining clips from metal mudguard.
- 2/ Vehicles with Factory fog lights—Remove fog lights from plastic bumper and remove fog lights from their original plastic holders.
- 3/ Vehicles with Factory Head light washers—Remove Head light washer external cap (Lift up head light washer cap and disconnect retaining clip to remove it).
- 4/ Attach the supplied steel mounting bracket in place of the original bumper reinforcement bar, using original bolts, do not tighten, as yet.
- 5/ Fit bullbar to vehicle & loosely bolt in place using M12 bolts, nyloc nuts, washers.
- 6/ Align as required and tighten ALL BOLTS.
- 7/ Trim original plastic splash guards to fit inside lower edge of bullbar and secure with screws provided.
- 8/ Fit supplied grill support brackets to radiator support panel and refit grill.
- 9/ **NOTE** :The following is NOT Required if fitting Subaxtreme Alloy Sumpguard.

The sumpguard protector covers and supports front edge of the original plastic sumpguard. Trim the front edge of the sump guard as per diagram below. Bolt the supplied sumpguard protector in place with existing 2 lower radiator support panel bolts which bolt front subframe to lower radiator support panel. Front edge of plastic sumpguard fits into the back of the protector.

* Trim off approx 10-15mm from front 3 edges of plastic sumpguard, so as to make front edge straighter when viewed from side of vehicle. This is to allow front edge of sumpguard to fit into supplied protector



Components

- 1 - Aluminium Bar
- 1 - Steel mounting bracket
- 2 - Grill support brackets
- 1 - Fitting instruction
- 1 - Sumpguard protector
- 6 - M12 x 35mm Bolts
- 6 - M12 Nyloc Nuts
- 6 - M12 Washers
- 2 - M8 bolts
- 2 - M8 Washers
- 2 - M8 Nuts
- 10-Self drilling screws